

CLAIMS

- ✓ 1. A cathode sub-assembly for an ion source comprising:  
an indirectly heated cathode; and  
a support rod fixedly attached to the indirectly heated cathode for supporting the  
5 cathode within an arc chamber of the ion source.
- ✓ 2. The cathode sub-assembly as defined in claim 1 wherein the support rod is attached  
to a surface of the cathode facing away from the arc chamber.
- 10 ✓ 3. The cathode sub-assembly as defined in claim 2 wherein the cathode is in the shape  
of a disk.
- ✓ 4. The cathode sub-assembly as defined in claim 3 wherein the support rod is fixedly  
15 attached at or near the center of the cathode, along an axis of the cathode.
- ✓ 5. The cathode sub-assembly as defined in claim 4 wherein the support rod is in the  
shape of a cylinder and the diameter of the cathode is larger than a diameter of the support  
rod.
- 20 ✓ 6. The cathode sub-assembly as defined in claim 5 wherein the diameter of the  
cathode is at least four times larger than the diameter of the support rod.
7. The cathode sub-assembly as defined in claim 5 further comprising a spring loaded  
clamp for holding the support rod.
- 25 ✓ 8. The cathode sub-assembly as defined in claim 1 wherein the support rod  
mechanically supports and conducts electrical energy to the cathode.
- Sub  
A<sub>1</sub>  
30 ✓ 9. A cathode assembly for use in an indirectly heated cathode ion source which  
includes an arc chamber housing that defines an arc chamber, comprising:  
a cathode sub-assembly, including a cathode and a support rod fixedly mounted  
thereto; and

a filament for emitting electrons, that is positioned outside the arc chamber in close proximity to the support rod of the cathode sub-assembly; and

a cathode insulator for electrically and thermally isolating the cathode from an arc chamber housing, that is disposed around the cathode of the cathode sub-assembly.

5

✓ 10. The cathode sub-assembly as defined in claim 9 further comprising a filament disposed around the support rod in close proximity to the cathode and isolated from a plasma in the arc chamber.

10

✓ 11. The cathode sub-assembly as defined in claim 9 further comprising a filament disposed around the support rod in close proximity to the cathode and isolated from a plasma in the arc chamber, wherein the filament is fabricated of an electrically conductive material and includes an arc-shaped turn having an inside diameter greater than or equal to the diameter of the support rod.

15

12. The cathode sub-assembly as defined in claim 9 further comprising a filament disposed around the support rod in close proximity to the cathode and isolated from a plasma in the arc chamber, wherein the filament is fabricated of an electrically conductive material and includes an arc-shaped turn having an inside diameter greater than or equal to the

20

diameter of the support rod, and wherein a cross-sectional area of the filament varies along a length of the filament, and is smallest along the arc-shaped turn.

13. The cathode assembly of claim 9 wherein said cathode insulator includes an opening having a diameter that is larger than or equal to the diameter of the cathode.

25

✓ 14. The cathode assembly as defined in claim 13 wherein a vacuum gap is provided between the cathode insulator and the cathode to limit thermal conduction.

15. The cathode insulator of claim 13 wherein said cathode insulator has a generally tubular shape with a sidewall and includes a flange, for shielding the sidewall of the cathode insulator from a plasma in the arc chamber.

Sub  
X2  
30

16. The cathode insulator of claim 15 wherein said flange is provided with a groove on a side of the flange facing away from the plasma, for increasing a path length between the cathode and the arc chamber housing.

5      ✓ 17. A method for supporting and indirectly heating a cathode of an ion source comprising steps of:

supporting the cathode by a rod fixedly attached to the cathode; and  
bombarding the cathode with electrons.

10

18. A cathode assembly for an ion source comprising:

a cathode;

a support rod fixedly attached to the cathode; and

a cathode insulator for electrically and thermally isolating the cathode from an arc chamber housing; and

15

an indirect heating means for indirectly heating the cathode.

10  
Sub 3  
✓  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100